

# MATERIAL SAFETY DATA SHEET

Viscosity Oil Company - Monroe® Shock Absorber Oil--All Grades

Effective Date: 6/25/08

Code: 013460

---

## Section I - PRODUCT AND COMPANY IDENTIFICATION

---

PRODUCT NAME: Monroe® Shock Absorber Oil -- All Grades

MANUFACTURER'S NAME:

Viscosity Oil Company

P.O. Box 2967

Houston, TX 77252-2967

EMERGENCY TELEPHONE NO.

(800) 546-6040

REVISION DATE:

00-00-00

---

## Section II - INGREDIENTS

---

Component Name	Hydrotreated Naphthenic Oil	Hydrotreated Light Paraffinic Distillate	Proprietary Additives	Alkyl Methacrylate Copolymer
Hazardous Percentage	-----	-----	-----	-----
Component	OSHA PEL	OSHA PEL	OSHA PEL	OSHA PEL
CAS NUMBER in Blend	64742-53-6 NO	64742-55-8 NO	Mixture NO	68171-46-0 NO
MIN MAX	75 to 85	15 to 20	2 to 3	1 to 3
Exposure Limit Units	ACGIH TLV NO LIMIT	ACGIH TLV NO LIMIT	ACGIH TLV NO LIMIT	ACGIH TLV NO LIMIT

---

## Section III - HEALTH EFFECT INFORMATION

---

**EYE CONTACT:** This product may be slightly irritating to the eyes upon direct contact. Based on testing of similar products and/or components.

**SKIN CONTACT:** Avoid skin contact. This product may cause slight skin irritation upon direct contact. Based on testing of similar products and/or components. Prolonged or repeated contact may result in contact dermatitis which is characterized by dryness, chapping, and reddening. This condition may make the skin more susceptible to other irritants, sensitizers, and disease.

Prolonged or repeated contact may result in oil acne which is characterized by blackheads with possible secondary infection. See health data section below.

**INHALATION:** This product has a low vapor pressure and is not expected to present an inhalation hazard at ambient conditions. Caution should be taken to prevent aerosolization or misting of this product. The Permissible Exposure Limit (PEL) and Threshold Limit Value (TLV) for this product as oil mist is 5 mg/m<sup>3</sup>. Exposures below 5 mg/m<sup>3</sup> appear to be without significant health risk. The short-term exposure limit for this product as an oil mist is 10 mg/m<sup>3</sup>.

**INGESTION:** Do not ingest. This product is relatively non-toxic by ingestion. This product has laxative properties and may result in abdominal cramps and diarrhea. See health data section below.

**HEALTH DATA:** On rare occasions, prolonged and repeated exposure to oil mist poses a risk of pulmonary disease such as chronic lung inflammation. This condition is usually asymptomatic as a result of repeated small aspirations. Shortness of breath and cough are the most common symptoms. The international agency for research on cancer has concluded that highly refined mineral oils are group 3 substances. "Not classifiable as to their carcinogenicity to humans," based on inadequate human and inadequate animal evidence. This substance is not carcinogenic according to the OSHA hazard communication standard.

---

#### **Section IV - EMERGENCY & FIRST AID PROCEDURES**

---

**EYE CONTACT:** Immediately flush eyes with large amounts of water and continue flushing until irritation subsides. If material is hot, treat for thermal burns and take victim to hospital immediately.

**SKIN CONTACT:** Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs, seek medical attention. If material is hot, submerge injured area in cold water. If victim is severely burned, remove to a hospital immediately.

**INHALATION:** This material has a low vapor pressure and is not expected to present an inhalation exposure at ambient conditions.

**INGESTION:** Do not induce vomiting. Seek medical attention.

---

#### **Section V - PERSONAL HEALTH PROTECTION INFORMATION**

---

**EYE PROTECTION:** Eye protection is not required under conditions of normal use. If material is handled such that it could be splashed into eyes, wear plastic face shield or splash-proof safety goggles.

**SKIN PROTECTION:** No skin protection is required for single, short duration exposures. For prolonged or repeated exposures, use impervious clothing (boots, gloves, aprons, etc.) over parts of the body subject to exposure. If handling hot material, use insulated protective clothing (boots, gloves, aprons, etc.). Launder soiled clothes. Properly dispose of contaminated leather articles including shoes, which cannot be decontaminated.

**RESPIRATORY PROTECTION:** Respiratory protection is not required under conditions of normal use. If vapor or mist is generated when the material is heated or handled. Use an organic vapor respirator with a dust and mist filter. All respirators must be

NIOSH certified. Do not use compressed oxygen in hydrocarbon atmospheres.

**VENTILATION:** If vapor or mist is generated when the material is heated or handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure or flammable limits.

**OTHER:** Consumption of food and beverage should be avoided in work areas where hydrocarbons are present. Always wash hands and face with soap and water before eating, drinking, or smoking.

---

## **Section VI - FIRE PROTECTION INFORMATION**

---

FLASH POINT:	154 C / 310 C
TEST METHOD:	COC ASTM D3278
AUTOIGNITION TEMPERATURE:	No data
TEST METHOD:	No data
FLAMMABLE LIMITS IN AIR % BY VOL:	
LOWER:	No Data
UPPER:	No Data

**EXTINGUISHING MEDIA:** Use dry chemical, foam, or carbon dioxide.

**SPECIAL FIRE FIGHTING PROCEDURES:** Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

**UNUSUAL FIRE AND EXPLOSIVE CONDITIONS:** Dense smoke may be generated while burning. Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

---

## **Section VII - REACTIVITY DATA**

---

STABILITY (THERMAL LIGHT, ETC.):	Stable
CONDITIONS TO AVOID:	None
HAZARDOUS POLYMERIZATION:	Will not occur
CONDITIONS TO AVOID:	None

**INCOMPATIBILITY MATERIALS TO AVOID:** May react with strong oxidizing agents

**HAZARDOUS DECOMPOSITION PRODUCTS:** None

---

## **Section VIII - ENVIRONMENTAL PRECAUTIONS**

---

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Consult health effect information in Section III, personal health protection information in Section V, fire protection information in Section VI, and reactivity data in Section VII. Notify appropriate authorities of spill. Contain spill immediately. Do not allow spill to enter sewers or watercourses. Remove all sources of ignition. Absorb with appropriate inert material such as sand, clay, etc. Large spills

may be picked up using vacuum pumps, shovels, buckets, or other means and placed in drums or other suitable containers.

**WASTE DISPOSAL METHOD:** All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded, may be a regulated waste. Refer to state and local regulations. Caution! If regulated solvents are used to clean up spilled material, the resulting waste mixture may be regulated. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. Waste material may be land filled or incinerated at an approved facility. Materials should be recycled if possible.

---

## **Section IX - MISCELLANEOUS**

---

**HANDLING AND STORAGE REQUIREMENTS:** Do not transfer to unmarked containers. Store in closed containers away from heat, sparks, open flame, or oxidizing materials. Fire extinguishers should be kept readily available. See NFPA 30 and OSHA 1910.106--Flammable and Combustible Liquids. This product is not a controlled substance under the Canadian WHMIS regulations.

**ADDITIONAL INFORMATION:** This mixture may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used. Pennzoil company must rely upon the hazard evaluation of such components submitted to Pennzoil by that product's manufacturer or importer. This product is not known to contain any SARA TITLE III, Section 313 reportable chemicals at or greater than 1.0% (0.1% for carcinogens). All ingredients of this product are listed on the toxic substances control act (TSCA) inventory.

DOT: Not regulated.  
VISCOSITY: 75 sus @ 100 F

---

## **Section X - PHYSICAL PROPERTIES**

---

BOILING POINT:	No data
MELTING POINT:	-51 C / -60 F
APPEARANCE:	Orange colored liquid
ODOR:	Mild petroleum odor
VAPOR PRESSURE:	< 0.1 mm hg @ rt
SOLUBILITY:	< 1% in water. Almost 100% in mineral oil
PERCENT VOLATILE:	Nil
VAPOR DENSITY (AIR = 1):	No data
EVAPORATION RATE (EE = 1):	< 0.1
SPECIFIC GRAVITY:	0.88
MOLECULAR WEIGHT:	No data